

do klase B 125

BG- FILCOTEN





spot



BG-FILCOTEN® spot

Dvorišni slivnik napravljen od FILCOTEN® HPC (Beton Visoke Performanse) – mogućnost prolaska automobila

Artikal br.	spot / klasa A 1 – mogućnost prolaska automobila	L/W/H	Težina	Kom/Pal
14130001	spot uklj. mrežastu rešetku od pocinkovanog čelika sa fix sistemom-samo zaključavanja, MW 25/2.5 mm, sabirno okno i koficu za sabirno okno	300/300/419	21.5 kg	16
14130020	spot sabirno okno	300/300/276	12.3 kg	18
14130023	spot sabirno okno uklj otvor DN 100	300/300/276	11.4 kg	18







spot sa mrežastom rešetkom sa mogućnošću prelaska automobila uklj. sifon i koficu, opcionalno sabirno okno

spot sabirno okno sa ili bez otvora za izliv DM 122

BG-FILCOTEN® spot

Dvorišni slivnik napravljen od FILCOTEN® HPC (Betona Visoke Performanse) uklj. liveno gvozdenu ivicu – do klase B 125

Artikal br.	spot sa liveno gvozdenom ivicom / klasa A15 – B 125	L/W/H	Težina	Kom/Pal
14130101	spot uklj. liveno gvozdenu ivicu, mrežastu rešetku od pocinkovanog čelika sa fiX-sistemom samo-zaključavanjem, MW 25/2.5 mm, sifonom i koficom	300/300/450	24.8 kg	16
14130102	spot uklj. liveno gvozdenu ivicu, liveno gvozdeno rešetku (EN-GJS) sa fix-sistemom samo-zaključavanja, radijalni dizajn, sifon i koficu	300/300/450	26.7 kg	16
14130020	spot sabirno okno	300/300/276	12.3 kg	18
14130023	spot sabirno okno uklj otvor DN 100	300/300/276	11.4 kg	18



spot uklj. liveno gvozdenu ivicu sa mrežastom rešetkom ili liveno gvozdenom rešetkom do klase B uklj. sifon i koficu
Opcionalno sabirno okno

spot sabirno okno sa ili bez otvora za izliv DM 122
Liveno gvozdenu ivicu se može transponovati

Reference



BG-FILCOTEN®

BG-CLASSIC

BG-FLEX

Specijalni proizvod

Uputstvo za ugradnju

